

## Conveyors

E-PAK Variable Speed Conveyors are built to fit your production needs and are available in a wide variety of lengths, widths, and construction types/materials. In addition to straight sections, 45°, 90° and 180°-curved configurations are available to maximize production efficiency

and fit space requirements. The modular design allows you to add complete conveyors or extensions to your existing production line. No matter what your packaging application may be, E-PAK will manufacture the right conveyor system to fit your needs.

# Conveyors

## Features

- Versatile design
- Robust construction
- Tool-less adjustments
- Customized per application

## Benefits

- Capacity to transport containers from 1/4 ounce up to 5 gallon pails
- Stainless steel and anodized aluminum construction protect your components for longer life. HDPE, UHMW, and PVC are also available for corrosives
- Reduce down-time with faster changeover
- Built to meet the specific requirements of a packaging line

---

## Standard Specifications

- Standard frames are 304 stainless steel
- Standard flat top chain available in acetal, polypropylene, or polyethylene
- Standard belt widths are 4.5", 7.5", 10" & 12" (custom sizes available)
- Section increment lengths are 30" or 60" and can also be added later to suit your growing needs
- Support stands are 304 stainless steel or polypropylene (for corrosive applications)
- Suited for standard line height between 32" and 38" (custom heights available)
- Finished size & weight capacities dependent on your application requirements

## Optional Components


- HDPE/PVC and 316 stainless steel construction available
- Sanitary models typically include closed frame, raised belt, and wash-down motor
- Hazardous construction components and controls for flammable products
- Corrosive contact and corrosive fume construction components and controls available
- Special applications are common for E-PAK, consult your E-PAK sales representative

## Applications


- Virtually any container up to 5 gallon
- Standard and custom designed conveyors can be used for almost any product including food and beverage, personal care, janitorial, pharmaceutical, molten, and many others

## Power Requirements

- UL listed NEMA 4/12/4X variable speed controller standard on stand-alone conveyors
- 115VAC, 1 phase, 60 Hz standard power requirement (other voltage/phase available)
- 90 volt DC motor standard, optional AC motor available
- Hazardous location electrical enclosure and components are available



Container spacing & transfer components available



Tool-less rail adjustments



1535 S. State Road 39  
LaPorte, IN 46350 U.S.A.  
Tel: (800) 328-0466 Fax: (219) 324-2884  
www.epakmachinery.com  
sales@epakmachinery.com



*Quality* ♦ *Value* ♦ *Excellence!*